

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1 1. (Currently amended) A method for facilitating use of a collation
2 element that supports a large number of characters, comprising:
3 receiving the collation element;
4 reading a primary weight value from a primary weight field within the
5 collation element;
6 if the primary weight value falls within a reserved set of values, reading an
7 additional portion of the primary weight value from a secondary weight field and a
8 tertiary weight field within the collation element; and
9 if the primary weight value is not within the reserved set of values,
10 reading a secondary weight value from the secondary
11 weight field within the collation element, and
12 reading a tertiary weight value from the tertiary weight field
13 within the collation element,
14 wherein the primary weight value identifies a character;
15 wherein the secondary weight value can specify an accent
16 on the character; and
17 wherein the tertiary weight value can specify case
18 information for the character.

- 1 2. (Original) The method of claim 1, wherein if the primary weight value
2 falls within a reserved set of values, the method additionally comprises:

3 setting the secondary weight value to a secondary default value; and
4 setting the tertiary weight value to a tertiary default value.

1 3. (Original) The method of claim 1, wherein the collation element adheres
2 to a structure specified in Unicode Technical Report No. 10.

1 4. (Canceled).

1 5. (Original) The method of claim 1, wherein the collation element is four
2 bytes in size, of which the primary weight field is two bytes, the secondary weight
3 field is one byte and the tertiary weight field is one byte, unless a value in the
4 primary weight field belongs to the reserved set of values, in which case the
5 primary weight field takes up all four bytes of the collation element.

1 6. (Currently amended) The method of claim 5, wherein the reserved set of
2 values for the primary weight value includes hexadecimal values 0xFFFF0-0xFFFF.

A1
1 7. (Original) The method of claim 1, wherein the collation element is taken
2 from a collation weight table that is used to map characters to collation weights in
3 order to establish an ordering between strings of characters.

1 8. (Original) The method of claim 7, further comprising constructing a
2 sorting key for a string by:
3 reading each character in the string;
4 looking up a corresponding collation element for each character from the
5 collation weight table; and
6 adding the corresponding collation element for each character to the
7 sorting key.

1 9. (Original) The method of claim 8,
2 wherein the sorting key is associated with a record within a database; and
3 wherein the sorting key is used to construct a linguistic index for the
4 database.

1 10. (Currently amended) A computer-readable storage medium storing
2 instructions that when executed by a computer cause the computer to perform a
3 method for facilitating use of a collation element that supports a large number of
4 characters, the method comprising:
5 receiving the collation element;
6 reading a primary weight value from a primary weight field within the
7 collation element;
8 if the primary weight value falls within a reserved set of values, reading an
9 additional portion of the primary weight value from a secondary weight field and a
10 tertiary weight field within the collation element; and
11 if the primary weight value is not within the reserved set of values,
12 reading a secondary weight value from the secondary
13 weight field within the collation element, and
14 reading a tertiary weight value from the tertiary weight field
15 within the collation element,
16 wherein the primary weight value identifies a character;
17 wherein the secondary weight value can specify an accent
18 on the character; and
19 wherein the tertiary weight value can specify case
20 information for the character.

1 11. (Original) The computer-readable storage medium of claim 10,
2 wherein if the primary weight value falls within a reserved set of values, the
3 method additionally comprises:

4 setting the secondary weight value to a secondary default value; and
5 setting the tertiary weight value to a tertiary default value.

1 12. (Original) The computer-readable storage medium of claim 10,
2 wherein the collation element adheres to a structure specified in Unicode
3 Technical Report No. 10.

1 13. (Canceled).

1 14. (Original) The computer-readable storage medium of claim 10,
2 wherein the collation element is four bytes in size, of which the primary weight
3 field is two bytes, the secondary weight field is one byte and the tertiary weight
4 field is one byte, unless a value in the primary weight field belongs to the reserved
5 set of values, in which case the primary weight field takes up all four bytes of the
6 collation element.

1 15. (Currently amended) The computer-readable storage medium of claim
2 14, wherein the reserved set of values for the primary weight value includes
3 hexadecimal values 0xFFFF0-0xFFFF.

1 16. (Original) The computer-readable storage medium of claim 10,
2 wherein the collation element is taken from a collation weight table that is used to
3 map characters to collation weights in order to establish an ordering between
4 strings of characters.

1 17. (Original) The computer-readable storage medium of claim 16,
2 wherein the method further comprises constructing a sorting key for a string by:
3 reading each character in the string;
4 looking up a corresponding collation element for each character from the
5 collation weight table; and
6 adding the corresponding collation element for each character to the
7 sorting key.

1 18. (Original) The computer-readable storage medium of claim 17,
2 wherein the sorting key is associated with a record within a database; and
3 wherein the sorting key is used to construct a linguistic index for the
4 database.

1 19. (Currently amended) An apparatus that facilitates use of a collation
2 element that supports a large number of characters, comprising:
3 an assignment mechanism that is configured to read a primary weight
4 value from a primary weight field within the collation element;
5 wherein if the primary weight value falls within a reserved set of values,
6 the assignment mechanism is configured to read an additional portion of the
7 primary weight value from a secondary weight field and a tertiary weight field
8 within the collation element; and
9 wherein if the primary weight value is not within the reserved set of
10 values, the assignment mechanism is configured to,
11 read a secondary weight value from the secondary weight
12 field within the collation element, and to
13 read a tertiary weight value from the tertiary weight field
14 within the collation element,
15 wherein the primary weight value identifies a character;

16 wherein the secondary weight value can specify an accent
17 on the character; and
18 wherein the tertiary weight value can specify case
19 information for the character.

1 20. (Original) The apparatus of claim 19, wherein if the primary weight
2 value falls within the reserved set of values, the assignment mechanism is
3 configured to:
4 set the secondary weight value to a secondary default value; and to
5 set the tertiary weight value to a tertiary default value.

1 21. (Original) The apparatus of claim 19, wherein the collation element
2 adheres to a structure specified in Unicode Technical Report No. 10.

1 22. (Canceled).

AI
1 23. (Original) The apparatus of claim 19, wherein the collation element is
2 four bytes in size, of which the primary weight field is two bytes, the secondary
3 weight field is one byte and the tertiary weight field is one byte, unless a value in
4 the primary weight field belongs to the reserved set of values, in which case the
5 primary weight field takes up all four bytes of the collation element.

1 24. (Currently amended) The apparatus of claim 23, wherein the reserved
2 set of values for the primary weight value includes hexadecimal values 0xFFFF0-
3 0xFFFF.

1 25. (Original) The apparatus of claim 19, wherein the collation element is
2 taken from a collation weight table that is used to map characters to collation
3 weights in order to establish an ordering between strings of characters.

1 26. (Original) The apparatus of claim 25, further comprising a key
2 construction mechanism for constructing a sorting key for a string, wherein the
3 key construction mechanism is configured to:

4 read each character in the string;

5 lookup a corresponding collation element for each character from the
6 collation weight table; and to

7 add the corresponding collation element for each character to the sorting
8 key.

1 27. (Original) The apparatus of claim 26,
2 wherein the sorting key is associated with a record within a database; and
3 wherein the sorting key is used to construct a linguistic index for the
4 database.